

# D-Ring Anchor

The D-ring anchor provides a compact, reliable connection point for your fall protection system that may be attached to the structure using fasteners or weld



**Model No.:**  
9501683

**Weight (approx):**  
0.6kg

**Materials:**  
• Forged alloy steel - yellow zinc plated

**Dimensions:**  
• External - H = 75mm, W = 45mm, L = 100mm  
• Internal - H = 57mm, L = 82mm  
• Thickness of D-ring = 13mm,  
• Thickness of D-ring = 10mm

## Mounting Requirements:

- Hole Size - 13mm
  - Fasteners - M12 Set Screw/Bolt
  - The anchor point must be installed to structure that is capable of withstanding Anchor Point Loads.
- Note: If there are any concerns about integrity of structure, it shall be investigated by an engineer.
- All mounting holes must be a 13mm clearance hole and must not be within 25mm from an edge

**Capacity:**  
One User - 136kg

**Rating:**  
22kN

**Compatibility:**  
DBI-SALA anchors are designed for use with DBI-SALA approved components or systems, or as recommended by a competent person.

**Standards:**  
AS/NZS 1891.4

**Country of Origin:**  
U.S.A.

## Special Instructions/Conditions of Use:

- Reading user instruction manual prior to use is essential.
- To be installed by a competent person
- Annual inspection & re-certification is required as per AS/NZS 1891.4.



Capital Safety - Australia & New Zealand  
Australia: 1800 245 002 | New Zealand: 0800 212 505  
[www.capitalsafety.com.au](http://www.capitalsafety.com.au)  
[sales@capitalsafety.com.au](mailto:sales@capitalsafety.com.au)

• Asia: +65 6558 7758 • Latin America: +1 651 385 4301  
• USA: 800.328.6146 • Northern Europe: +44 (0) 1928 571234  
• Canada: 800 387 7484 • Germany: +49 2634 8052  
• Europe, Middle East, Africa: +33 (0)4 97 10 00 10

